



Earth Bonding Point (EBP) includes 2,0 m earthing cable with a 4 mm ring terminal (1 Mohm resistor for every input).

| Part Nr. | |
|----------------|--|
| 2200.121.10 | 2 x 10 mm snaps and 1 x 4 mm; banana plug socket |
| 2200.121.10.1 | With 3 x 10 mm snaps |
| 2200.121.10.2 | With 1 x 10 mm snap and 2 x 4 mm banana plug sockets |
| 2200.W.3 | Yellow, right angle with 3 x 10 mm snaps |
| 2200.121.10.13 | 2 x plug socket for 3M system; 1 x 10 mm snap |
| 2200.W.5 | 1 x 10 mm snap; 2 x 4 mm banana plug socket |

GROUNDING PLUG



Used for direct and easy mat grounding

| Part Nr. | |
|----------|---|
| 2200.110 | Without cable, banana plug socket, without resistor |
| 2200.111 | With 2,4 m coil cord, 1 Mohm safety resistor and a 10 mm snap |
| 2200.113 | 2 m flat cable, 4 mm ring terminal, without resistor |
| 2201.230 | Without cable, 1 MOhm resistor; 3 x 10 mm snap |
| 2201.245 | Without cable, 1 MOhm resistor; 2 x 10 mm snap, 1 x screwed connection for 4 mm ring terminal |
| 2201.258 | Without cable, 1 MOhm resistor; 1 x 10 mm snap, 2 x 4 mm banana plug socket |

