SAFESHIELD[®] SHIPPING BOXES

The Safeshield shipping cardboard boxes provide a high protection against electrostatic discharge and against electrostatic fields. They are ideal for packing, stocking and shipping ESD sensitive components (ESDS).




5,0m 4,0m

3,0m 2,0m 1,0m

E ^{1,0m}

IEC EN 133

- High shielding performance due to highly conductive inner layer
- Inner and outer permanent static dissipative layers
- Good mechanical properties
- Recyclable
- Reusable
- Non-corrosive
- No heavy metals
- Colour: Blue
- Print: ESD and Resy symbols, warning note in German and English
- UV resistant



E = 0,1986 nJoule (198,6 pJoule)

> Energy test with Safeshield® shipping boxes according to HBM test method with 1.000 V

Energy test without shielding.

SAFESHIELD[®] STACKING BOX



- Rugged construction
- Safe transport stacking design
- Closed handholds, with print, delivered flat

time [s]

Cover:

Finish with 4-point-gluing

Part Nr.	Outer Dim. mm (D x W x H)	Inner Dim. mm (D x W x H)
Stacking Box		
5510.SB.400.A	385 x 275 x 105 mm	360 x 250 x 100 mm
5510.SB.400.B	385 x 275 x 215 mm	360 x 250 x 210 mm
5510.SB.600.A	575 x 385 x 105 mm	550 x 360 x 100 mm
5510.SB.600.B	575 x 385 x 215 mm	550 x 360 x 210 mm
Cover		
5510.SB.43		390 x 280 x 40 mm
5510.SB.64		580 x 390 x 40 mm



IEC EN