

UTILITY CART WITH FOLDABLE HANDLE

NEW



- Stainless steel construction
- 4 conductive castors: Ø 100 mm
- Includes 4 swivel rubber castors, 2 castors with brake
- Platform fitted with dissipative ECOSTAT® Anti slip mat
- Overall load bearing: 100 kg for a uniformly distributed load
- ESD symbol
- For self assembly

IEC
EN

Part Nr.	Dimensions
5390.KW.N	825 x 520 x 950 mm (L x W x H)

UTILITY CARTS

NEW



- Made of galvanized steel
- Conductive swivel castors
- Rubber castors
- Silent and smooth operation
- 4 conductive swivel castors, 2 with brake
- ESD symbol
- For self assembly
- **1 shelf**, fitted with dissipative ECOSTAT® Anti slip mat
- Shelf height: 180 mm
- Overall load bearing up to 125 kg for a uniformly distributed load
- Suitable for PCB racks transport
- castors Ø 100 mm

IEC
EN

Part Nr.	Dimensions
5390.510.N	950 x 540 x 915 mm (L x W x H)

UTILITY CART



- Made of galvanized steel
- Conductive swivel castors
- Rubber castors
- Silent and smooth operation
- 4 conductive swivel castors, 2 with brake
- ESD symbol
- For self assembly
- **2 shelves**, fitted with table mats,
- Highest shelf 730 mm
- Overall load bearing up to 150 kg for a uniformly distributed load
- Distance between shelves: 520 mm
- castors Ø 100 mm
- 3rd shelf optional, Distance between shelves: 250 mm

IEC
EN

Part Nr.	shelf
5390.400	740 x 430 mm
5390.400.A	3rd shelf