



- Made of galvanized steel
- Conductive swivel castors
- Rubber castors
- Silent and smooth operation
- 4 conductive swivel castors, 2 with brake
- ESD symbol
- For self assembly
- **3 shelves**, fitted with table mat
- Highest shelf, 770 mm
- Overall load bearing up to 250 kg for a uniformly distributed load
- Distance between shelves: 260 mm
- castors Ø 125 mm

IEC  
EN

Part Nr.	shelf
<b>5390.700</b>	950 x 540 mm

# TRANSPORT CART



- Stable steel construction
- Dissipative powder coating
- Colour: grey - RAL 7035
- Frame profile 40 x 40 mm
- 5 metal shelves – 3 shelves are height adjustable
- Shelf height 255 – 1710 mm adjustable
- Load bearing of up to 120 kg for a uniformly distributed load for each shelf
- 4 conductive castors: Ø 160 mm
- 2 conductive swivel castors with brake
- Overall load bearing: 400 kg
- ESD symbol
- For self assembly

IEC  
EN

Part Nr.	Dimension
<b>5390.T</b>	1000 x 600 x 1760 mm (L x W x H)
Boxes not included	

# TRANSPORT CART



- Dissipative, powder coated steel construction
- Colour: grey - RAL 7035
- Frame profile 30 x 30 mm
- Easy snap- and screw fastening
- 4 galvanized shelves in 50mm distance, height adjustable
- Shelf height 250 to 1570 mm adjustable
- Load bearing of up to 80 kg for a uniformly distributed load for each shelf
- Easy handling
- 4 conductive castors; Ø 125 mm
- 2 conductive swivel castors with brake
- Overall load bearing: 250 kg
- ESD symbol

IEC  
EN

Part Nr.	Dimension
<b>5390.V</b>	1030 x 600 x 1660 mm (L x W x H)
Boxes not included	