

conductive
backing

- Two layer material
- Rugged synthetic rubber
- Resistant to solder and heat
- Abrasion resistant
- Elastic
- Volume conductive
- Thickness: 2 mm
- Includes 2 x 10 mm snap fastener and rounded edges*



Profile

IEC
EN




Part Nr.	Colour	Standard Sizes
1402.662.L*	Beige	610 x 1220 mm
1402.662.S*	Beige	610 x 900 mm
1402.662.R		rolls: 1220 mm x 10 m
1402.662.R10		rolls: 1000 mm x 10 m
1402.662.R61		rolls: 610 mm x 10 m
1402.662.Z		Custom sizes available on request

*rounded edges (radius approx. 43 mm)



Part Nr.	Colour	Standard Sizes
1402.663.L*	Platinum grey	610 x 1220 mm
1402.663.S*	Platinum grey	610 x 900 mm
1402.663.R		rolls: 1220 mm x 10 m
1402.663.R10		rolls: 1000 mm x 10 m
1402.663.R61		rolls: 610 mm x 10 m
1402.663.Z		Custom sizes available on request

*rounded edges (radius approx. 43 mm)



Part Nr.	Colour	Standard Sizes
1402.664.L*	Green	610 x 1220 mm
1402.664.S*	Green	610 x 900 mm
1402.664.R		rolls: 1220 mm x 10 m
1402.664.R61		rolls: 610 mm x 10 m
1402.664.Z		Custom sizes available on request

*rounded edges (radius approx. 43 mm)



Part Nr.	Colour	Standard Sizes
1402.665.L*	Light blue	610 x 1220 mm
1402.665.S*	Light blue	610 x 900 mm
1402.665.R		rolls: 1220 mm x 10 m
1402.665.R10		rolls: 1000 mm x 10 m
1402.665.R61		rolls: 610 mm x 10 m
1402.665.Z		Custom sizes available on request

*rounded edges (radius approx. 43 mm)