



- Metallic support 40 x 40 x 2 mm
- Reinforced metallic construction
- Workbench adjustable height between 750 and 950 mm
- Conductive grey paint finish
- Benchtop made of conductive chipboard and static dissipative hard laminate
- Includes 1 earth connecting box with 2 x 10 mm snaps and 1 x 4 mm banana plug socket
- Not mounted

IEC
EN

Part Nr.	Standard dimensions (W x D x H)
1950.LC.3906	1200 x 800 x 750 - 950 mm
1950.LC.3036	1250 x 800 x 750 - 950 mm
1950.LC.3056	1500 x 800 x 750 - 950 mm
1950.LC.3916	1600 x 800 x 750 - 950 mm
1950.LC.3086	1750 x 800 x 750 - 950 mm
1950.LC.3116	2000 x 800 x 750 - 950 mm

SHELVES



- Shelf unit with 2 or 3 supports, height: 350 mm
- Can be mounted on a benchtop (incl. screws)
- Top side coated with dissipative melamine resin, depth: 300 mm, thickness: 25 mm
- Dissipative powder coating
- Maximum load 60 kg

IEC
EN

Part Nr.	Standard dimensions	supports
1950.LZ.8333	1200 mm length	2
1950.LZ.8334	1250 mm length	3
1950.LZ.8335	1500 mm length	3
1950.LZ.8336	1600 mm length	3
1950.LZ.8337	1750 mm length	3
1950.LZ.8338	2000 mm length	3