

WORKBENCHES MELAMINE RESIN COATED HEIGHT ADJUSTABLE VERSION



- Metallic support, 50 x 40 mm with 2 rugged frames
- Workbench adjustable height between 763 and 873 mm
- Dissipative powder coating
- Benchtop made of conductive chipboard and static dissipative melamine resin
- Includes 1 earth connecting box with 2 x 10 mm snaps and 1 x 4 mm banana plug socket
- Suitable for light mechanical work
- Not mounted

IEC
EN

Part Nr.	Standard dimensions (W x D x H)
Standard table	
1950.LU.4018	1000 x 800 x 763 – 873 mm
1950.LU.4038	1250 x 800 x 763 – 873 mm
1950.LU.4058	1500 x 800 x 763 – 873 mm
1950.LU.4088	1750 x 800 x 763 – 873 mm
1950.LU.4118	2000 x 800 x 763 – 873 mm
Extension table (Standard table required!)	
1950.LU.6018	1000 x 800 x 763 – 873 mm
1950.LU.6038	1250 x 800 x 763 – 873 mm
1950.LU.6058	1500 x 800 x 763 – 873 mm
1950.LU.6088	1750 x 800 x 763 – 873 mm
1950.LU.6118	2000 x 800 x 763 – 873 mm

ALUMINIUM POSTS



- 4 sides selection
- Anodized aluminium profile 45 x 45 mm continuously adjustable height, profile length 1950 mm
- Usable height app. 1500 mm
- Flexible repositioning system
- Cross connecting bar
- Sliding rail frame
- Sliding rail
- Height: 2100 mm



Suitable only for tables
Part Nr. 1950.LU.XXX

Part Nr.	Dimensions	suitable for table width
1950.LU.8312	1235 x 655 x 1950 mm	1250 mm
1950.LU.8313	1485 x 655 x 1950 mm	1500 mm
1950.LU.8315	1735 x 655 x 1950 mm	1750 mm
1950.LU.8316	1985 x 655 x 1950 mm	2000 mm