


## EPA WORK PLACE LIGHTING Taneo LED



without swivel arm (SARL)



with swivel arm (SARKL)

- Chassis made of aluminum with ESD coating
- Colour temperature 4.700 to 5.300 K
- Continuously dimmable down to 10%
- 30 % energy savings
- Power supply: 100-240 V, 50/60Hz
- Mounting: with mounting bracket (horizontal)

## Part Nr.

**1930.TANEO.SARL** TANEO without swivel arm, 24 LEDs

**1930.TANEO.SARKL** TANEO with swivel arm, 12 LEDs

## EPA WORK PLACE LIGHTING TAMETO LED



- Chassis made of aluminum and plastic with ESD coating
- Colour temperature 4.000 K, approx. 23 W
- Rocker switch
- Power supply: 220-240 V, 50/60Hz
- Mounting: with mounting bracket

## Part Nr.

**1930.TAMETO.SAHKQ** TAMETO, 2 LED modules

## EPA WORK PLACE LIGHTING Taneo LED



- Made of static dissipative material
- Colour temperature 4.000 K to 5.000 K
- Continuously dimmable down to 10%
- 30 % energy savings
- Grounding with 10 mm snap
- Power supply: 100-240 V, 50/60Hz
- Mounting: with mounting clamp

## Part Nr.

**1930.TANEO.STZL** TANEO, 24 LED's

**1930.K** Mounting clamp, span 0-65 mm

**1930.K.2** Mounting clamp, span 65-135 mm