



Earth Bonding Point (EBP) includes 2,0 m earthing cable with a 4 mm ring terminal (1 Mohm resistor for every input).

Part Nr.	
2200.121.10	2 x 10 mm snaps and 1 x 4 mm; banana plug socket
2200.121.10.1	With 3 x 10 mm snaps
2200.121.10.2	With 1 x 10 mm snap and 2 x 4 mm banana plug sockets
2200.W.3	Yellow, right angle with 3 x 10 mm snaps
2200.121.10.13	2 x plug socket for 3M system; 1 x 10 mm snap
2200.W.5	1 x 10 mm snap; 2 x 4 mm banana plug socket

GROUNDING PLUG



Used for direct and easy mat grounding

Part Nr.	
2200.110.Y	Without cable, banana plug socket, without resistor
2200.111.Y	With 2,4 m coil cord, 1 Mohm safety resistor and a 10 mm snap
2200.113.Y	2 m flat cable, 4 mm ring terminal, without resistor
2200.115.Y	With 4,5 m flat cable, 1 Mohm safety resistor and a 10 mm snap (with protective cap)
2201.230	Without cable, 1 MOhm resistor; 3 x 10 mm snap
2201.245	Without cable, 1 MOhm resistor; 2 x 10 mm snap, 1 x screwed connection for 4 mm ring terminal
2201.258	Without cable, 1 MOhm resistor; 1 x 10 mm snap, 2 x 4 mm banana plug socket