



video



Cable reel, 50 m,
available on request.
Part Nr. 7100.2000.TR50



Metriso® B530 - test kit includes: digital high resistance tester, 2 probes model 870 with extension, a hand-held probe with connecting cable, user's instructions in German, English and French, calibration certificate, conductive carrying case fitted with dissipative pink foam.

- Suitable for resistance point-to-point and resistance to ground measurements
- Test voltage / Test current:
Ohmic range: $1 \text{ mA} \leq I \leq 1,3 \text{ mA}$
High ohmic range: DC 10 volts, 100 volts and 500 volts
- Test range:
Low ohmic range: 1 Ohm to 9,99 KOhm
High ohmic range: 1 kOhm to 199 GOhm
- Operation: Battery operated
- Probes: 2 x Model 870 (weight: 2,27 kg / Ø 63,5 mm) with conductive rubber (grey) and extension, 1 x hand-held probe Model 45

complies with IEC 61340-4-1, IEC 61340-2-3, IEC 61340-4-5

IEC
EN

Part Nr.

7100.B530.MK	Metriso® B530 Basic Test-Kit
7100.B530.G	Metriso® B530 Basic, instrument only
7100.B530.MK.850	Metriso® B530 Basic Test-Kit with probe model 850

NEW

THERMO-HYGROMETER TF-530



Digital thermo-hygrometer, ideal for fast and precise measurement of temperature and humidity.

- MAX/MIN/HOLD-function
- Backlight
- Automatic shutdown
- Tripod thread 1/4"
- Measuring range:
Temperature: $-30 \dots +70^\circ\text{C}$
Humidity: 0 ... 100%
- Dimension: 165 x 52 x 35 mm (L x W x H)
- Weight: 115g (without Battery)

Includes:
Meter, 9 V-Battery, Leather Case, Manual (german/english), calibration certificate

Part Nr.

7100.TF530	Digital Thermo-Hygrometer TF-530
-------------------	----------------------------------

