

PGTest STATION

Magnetic document holder made of IDP-STAT® - PVC in size DIN A3. Usable for various labeling options.



application example



Video



Test: OK



Test: FAIL

- Test station for PGT®120 or PGT®120.COM
- Dimensions: 1700 x 590 x 730 mm (H x W x D)
- **PGT®120 and printer are not included.**

Part Nr.

7100.PGT120.TEST.V01

PGTest Station for PGT®120 / PGT®120.COM with magnetic document holder made of IDP-STAT-PVC in size DIN A3, incl. wall mounted container

7100.PGT120.TEST.V18

PGTest Station for PGT®120.COM with Touchscreen-data terminal and temperature/humidity sensor incl. wall mounted container

PGT®120.COM WITH RS232 INTERFACE

The PGT®120.COM is a special version of the Personnel Grounding Tester PGT®120 and includes an additional RS232 interface.

The RS232 interface is able to process measurement data and test results in ASCII like time attendance systems.

- Adjustable door opening time (1 second or 3 seconds)
- Power supply: external power supply unit 230V AC / 12 V

Description of Interface:

- A computer or a terminal can be connected to the serial RS232 interface. Data is available in ASCII format, a computer with terminal program is sufficient to monitor measurement data in plain text.

Data:

- value footwear in series: value in kOhm
- value wrist strap system: value in kOhm
- value left foot: value in kOhm
- value right foot: value in kOhm
- test OK: OK
- test failed: Error no.

Includes:

PGT®120.COM, footwear testing electrode, calibration certificate, operating instructions (german/english), power supply 230 V AC / 12 V



Part Nr.

7100.PGT120.COM Special version PGT®120.COM with RS232-interface

IEC
EN



PGT®120 accessories see page 81