

## SRM®200



Built-in bar electrodes  
with conductive rubber



Pocket size surface resistance meter with LCD display. Includes conductive carrying case, grounding cord, USB-Cable, calibration certificate and software for reading the saved test data.

- Integrated temperature- and humidity-sensor
- Test range:  $10^3 - 10^{12}$  ohm
- Test voltage: open circuit voltage 100 V
- Operation: Battery operated
- Display: LCD-Display
- Probes: Built-in electrodes with conductive rubber

- with memory and USB connection to PC
- 2 external probes connection possible

IEC  
EN

## Part Nr.

<b>7100.SRM200.K</b>	Surface Resistance Meter SRM® 200
<b>7100.SRM110.L</b>	connecting cables, 2 x 1 m

## SRM®200 – VERIFICATION KIT



sample applications



Verification Kit for measuring conductive and dissipative surfaces.

Includes:

- 1 SRM®200 with various cables (Part Nr. 7100.SRM200.K)
- 2 Flat Probes Model 820
- 1 Mini Probe Modell 410
- 1 Hand-held probe Modell 45
- 2 connecting cables
- Calibration certificate
- Conductive carrying case



Video

IEC  
EN

## Part Nr.

<b>7100.SRM200.VK</b>	SRM®200 – verification kit
-----------------------	----------------------------