



- For the point to point measurement on small packaging and inside cavities
- Conductive rubber electrodes ($R < 20 \text{ ohm}$)
- Spring loaded mechanism for good contact
- Quick removable head
- Complies with IEC 61340-2-3
- Incl. calibration certificate

IEC
EN

Part Nr.

7220.840.SET	Miniprobe Set Model 840 incl. conductive carrying case and a 2 point probe tip/model 844
7220.844.1	Replacement pins for probe tip 844 (unit: 2 pcs)
7220.844.C	Calibration Unit for Two-Point-Probe, incl. calibration certificate
7220.841	Probe tip „mini ring probe“ (optional for 7220.840.SET), incl. calibration certificate

PRESS DOWN PROBE MODEL 830



- Very light and universally usable probe for resistance to ground measurements, point-to-point measurements, surface resistance- and volume resistance measurements.
- Conductive rubber ($R < 5 \text{ Ohm}$) with silver particles
- Circle – and concentric ring probe as magnetic interchangeable unit
- The standard weight of 2,5 kg is reached by pushing down the spring loaded mechanism
- Includes stainless steel plate, insulative plate, conductive carrying case and calibration certificate

Complies with:
IEC 61340-4-1
IEC 61340-2-3

IEC
EN

Part Nr.

7220.830.SET	Press Down Probe Model 830
---------------------	----------------------------